



Rohre

Nahtlose Edelstahlrohre

Technische Lieferbedingungen gemäß

DIN 17458 PK1/PK2

PED 97 / 23-GG

ASTM A /ASME SA 312/269

APZ EN 10204/ 3.1B AD W 2000

Abmessung		Gewicht	Bund	Lagerstandard	
NPS x SCH	Ad x s			TP 304L	TP 316L
Zoll	mm	Kg/m	m		
3/8 x 10s	17.15 x 1.65	0,64	528		
1/2 x 5s	21.34 x 1.65	0,81	348		
10s	2,11	1,01	348	•	•
40s	2,77	1,29	348	•	•
3/4 x 5s	26.67 x 1.65	1,04	318		
10s	2,11	1,30	318	•	•
40s	2,87	1,71	18	•	•
1 x 5s	33.41 x 1.65	1,31	318	•	•
10s	2,77	2,13	318	•	•
40s	3,38	2,54	318	•	•
1 1/4 x 5s	42.16 x 1.65	1,68	144	•	•
10s	2,77	2,74	144	•	•
40s	3,56	3,44	144	•	•
1 1/2 x 5s	48.26 x 1.65	1,93	222	•	•
10s	2,77	3,16	222	•	•
40s	3,68	4,11	222	•	•
2x 5s	60.33 x 1.65	2,42	222	•	•
10s	2,77	3,99	222	•	•
40s	3,91	5,52	222	•	•
2 1/2 x 5s	73.05 x 2.11	3,75	114		
10s	3,05	5,34	114	•	•
3 x 5s	88.90 x 2.11	4,59	114	•	•
10s	3,05	6,56	114	•	•
40s	5,49	11,47	114	•	•
3 1/2 x 10s	101.60 x 3,05	7,53	60	•	•
4 x 5s	114.30 x 2.11	5,93	114	•	•
10s	3,05	8,50	114	•	•
40s	6,02	16,32	60	•	•
5 x 5s	141.30 x 2,77	9,61	60		
10s	3,40	11,74	60	•	•
6 x 5s	168.28 x 2,77	11,48	144	•	•
10s	3,40	14,04	144	•	•
40s	7,11	28,70	36	•	•



Rohre

Geschweite Edelstahlrohre, geglht, gebeizt

Technische Lieferbedingungen gem

ANSI B 36.19(36.10)

ASTM A 312/999

bis 4" SCH 40s Innennaht geglttet

APZ EN 10204/ 3.1B AD W 2000

Abmessung		Gewicht	Bund	Lagerstandard	
NPS x SCH	Ad x s			TP 304L	TP 316L
Zoll	mm	Kg/m	m		
3/8 x 10s	17.15 x 1.65	0,64	528		
1/2 x 5s	21.34 x 1.65	0,81	348		
10s	2,11	1,01	348	•	•
40s	2,77	1,29	348	•	•
3/4 x 5s	26.67 x 1.65	1,04	318		
10s	2,11	1,30	318	•	•
40s	2,87	1,71	18	•	•
1 x 5s	33.41 x 1.65	1,31	318	•	•
10s	2,77	2,13	318	•	•
40s	3,38	2,54	318	•	•
1 1/4 x 5s	42.16 x 1.65	1,68	144	•	•
10s	2,77	2,74	144	•	•
40s	3,56	3,44	144	•	•
1 1/2 x 5s	48.26 x 1.65	1,93	222	•	•
10s	2,77	3,16	222	•	•
40s	3,68	4,11	222	•	•
2 x 5s	60.33 x 1.65	2,42	222	•	•
10s	2,77	3,99	222	•	•
40s	3,91	5,52	222	•	•
2 1/2 x 5s	73.05 x 2.11	3,75	114		
10s	3,05	5,34	114	•	•
3 x 5s	88.90 x 2.11	4,59	114	•	•
10s	3,05	6,56	114	•	•
40s	5,49	11,47	114	•	•
3 1/2 x 10s	101.60 x 3,05	7,53	60	•	•
4 x 5s	114.30 x 2.11	5,93	114	•	•
10s	3,05	8,50	114	•	•
40s	6,02	16,32	60	•	•
5 x 5s	141.30 x 2,77	9,61	60		
10s	3,40	11,74	60	•	•
6 x 5s	168.28 x 2,77	11,48	144	•	•
10s	3,40	14,04	144	•	•
40s	7,11	28,70	36	•	•